

UTILITY PATENT APPLICATION TRANSMITTAL

(Filing of Continuation Application Under 35 U.S.C. §111(a))

Attorney Docket No. 826.1629/JDH

First Named Inventor or Application Identifier:

Yasuhiro KAWAKATSU, et al.

Express Mail Label No.

J0641 U.S. PTO
09/675049**APPLICATION ELEMENTS**

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: **Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231**

1. ☒ Fee Transmittal Form
2. ☒ Specification, Claims & Abstract [Total Pages: 72]
3. ☒ Drawing(s) (35 USC 113) [Total Sheets: 26]
4. ☒ Oath or Declaration [Total Pages: 3]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed)
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation by Reference (usable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) [] Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 [] Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14. ☐ Small Entity Statement(s) [] Statement filed in prior application, status still proper and desired.
15. ☒ Certified Copy of Priority Document(s) (if foreign priority is claimed) HEI 10-062742, filed March 13, 1998
16. ☒ Other: PCT/IPEA/409; PCT/ISA/210.

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☒ Continuation [] Divisional [] Continuation-in-part (CIP) of prior application No: PCT/JP99/01153
This continuing application is filed under 35 U.S.C. §111(a), based upon International Application PCT/JP99/01153, filed March 10, 1999, it being further noted that priority is based upon Japanese Patent Application 10-195604, filed July 10, 1998.

18. CORRESPONDENCE ADDRESS

21171

PATENT TRADEMARK OFFICE

NEW APPLICATION FEE TRANSMITTAL

Attorney Docket No. 826.1629/JDH
Application Number To be assigned
Filing Date September 28, 2000

AMOUNT ENCLOSED \$1,354.00

First Named Inventor Yasuhiro KAWAKATSU, et al.

FEE CALCULATION (fees effective 12/29/99)

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS	19 - 20 =	0	X \$ 18.00 =	\$ 0.00
	INDEPENDENT CLAIMS	11 - 3 =	8	X \$ 78.00 =	624.00
	MULTIPLE DEPENDENT CLAIMS (any number; if applicable)			+ \$260.00 =	
	BASIC FILING FEE				690.00
	Total of above Calculations =				\$ 1,314.00
	Surcharge for late filing fee, Statement or Power of Attorney (\$130.00)				+
	Reduction by 50% for filing by small entity (37 CFR 1.9, 1.27 & 1.28).				-
	TOTAL FILING FEE =				\$ 1,314.00
	Surcharge for filing non-English language application (\$130.00; 37 CFR 1.52(d))				+
	Recordation of Assignment (\$40.00; 37 CFR 1.21(h)(1))				\$40.00
	TOTAL FEES DUE =				\$ 1,354.00

METHOD OF PAYMENT

- ☒ Check enclosed as payment.
☐ Charge "TOTAL FEES DUE" to the Deposit Account No., below.
☐ No payment is enclosed and no charges to the Deposit Account are authorized at this time.

GENERAL AUTHORIZATION

- ☒ If the above-noted "AMOUNT ENCLOSED" is not correct, the Commissioner is hereby authorized to credit any overpayment or charge any additional fees necessary to:

Deposit Account No.


19-3935

Deposit Account Name

STAAS & HALSEY LLP

- ☒ The Commissioner is also authorized to credit any overpayments or charge any additional fees required under 37 CFR 1.16 (filing fees) or 37 CFR 1.17 (processing fees) during the prosecution of this application, including any related application(s) claiming benefit hereof pursuant to 35 USC § 120 (e.g., continuations/divisionals/CIPs under 37 CFR 1.53(b) and/or continuations/divisionals/CPAs under 37 CFR 1.53(d)) to maintain pendency hereof or of any such related application.

SUBMITTED BY: STAAS & HALSEY LLP

Typed Name	James D. Halsey, Jr.	Reg. No.	22,729
Signature		Date	September 28, 2000

APPLICATION FOR
UNITED STATES LETTERS PATENT
SPECIFICATION

INVENTOR(s): Yasuhiro KAWAKATSU and Yuuichirou IKEDA

Title of the Invention: DYNAMIC IMAGE COMPOSITION APPARATUS
AND METHOD

Dynamic Image Composition Apparatus and Method

Cross Reference to Related Application

This application is a continuation of
5 International PCT Application No. PCT/JP99/01153
filed on March 10, 1999.

Background of the Invention

Field of the Invention

10 The present invention relates to a dynamic
image composition apparatus for combining one or
more dynamic images and displaying them on a screen
and a method thereof.

15 Description of the Related Art

Recently, with the spread of personal
computers and workstations, the number of users who
use the reproduction software of dynamic image data
to reproduce an image while moving the image on a
20 screen has been increasing. Conventional
reproduction software has a function to combine and
store both the data of an image component to be
displayed and the data of the movement and to transmit
the combined data to a plotting device when the image
25 is reproduced.

However, when a complex movement, such as when an image component moves while vertically vibrating, is reproduced, a last movement must be manually composed in advance. Therefore, to represent a plurality of different complex movements when an image is reproduced, all kinds of movements are composed in advance and each image component is displayed according to a respective predetermined movement when the image is reproduced. Even when a plurality of image components are composed of the same movement element, such as translation, etc., each movement must be individually composed.

As described above, in the conventional reproduction software, a great amount of movement data must be prepared to represent many complex movements. A new movement cannot also be composed when an image is reproduced, nor can a movement also be flexibly modified. Furthermore, the conventional reproduction software has a problem that there is no method for sharing the same movement element with a plurality of image components.

Summary of the Invention

It is an object of the present invention to provide a dynamic image composition apparatus for

improving the versatility of each movement element and for easily representing a complex movement when displaying a plurality of dynamic images on a screen and a method thereof.

5 the dynamic image composition apparatus of the present invention comprises a plurality of plot information generating devices, one or more image management devices and a plotting device, and it combines and displays one or more images.

10 Each plot information generating device generates plot information used to plot a dynamic image. Each image management device manages the image data of each image and generates the plot information at a present time of each image by combining one
15 or more pieces of plot information generated by one or more of a plurality of plot information generating devices. The plotting device receives both the image data and plot information at a present time from
20 based on the plot information at a present time.

Brief Description of the Drawings

Fig. 1 shows the basic configuration of the dynamic image composition apparatus of the present
25 invention;

Fig. 2 shows the configuration of the first dynamic image composition apparatus;

Fig. 3 shows the configuration of the second dynamic image composition apparatus;

5 Fig. 4 shows the configuration of the third dynamic image composition apparatus;

Fig. 5 shows the configuration of the fourth dynamic image composition apparatus;

10 Fig. 6 shows the first dynamic image composition;

Fig. 7 is a flowchart showing the first plot update process;

Fig. 8 is a flowchart showing an event process;

15 Fig. 9 is a flowchart showing the first plot information generating process;

Fig. 10 is a flowchart showing a plot information function obtaining process;

Fig. 11 shows the second dynamic image composition;

20 Fig. 12 is a flowchart showing the second plot information generating process;

Fig. 13 shows a plot information string;

Fig. 14 is a flowchart showing a plot information string obtaining process;

25 Fig. 15 shows the third dynamic image

composition;

Fig. 16 is a flowchart showing the second plot update process;

Fig. 17 is a flowchart showing the third plot
5 information generating process;

Fig. 18 shows the fourth dynamic image composition;

Fig. 19 is a flowchart showing the fourth plot information generating process;

10 Fig. 20 shows the first dynamic image;

Fig. 21 shows the fifth dynamic image composition;

Fig. 22 shows the second dynamic image;

Fig. 23 shows the third dynamic image;

15 Fig. 24 shows the configuration of an information processing device;

Fig. 25 shows an example of storage media; and

Fig. 26 shows the configuration of the fifth dynamic image composition apparatus.

20

Description of Preferred Embodiments

The preferred embodiments of the present invention are described in detail below with reference to the drawings.

25 Fig. 1 shows the basic configuration of the

dynamic image composition apparatus of the present invention. The dynamic image composition apparatus shown in Fig. 1 comprises a plurality of plot information generating devices 1, one or more image management devices 2 and a plotting device 3, and it combines and displays one or more images.

Each plot information generating device 1 generates plot information used to plot a dynamic image. Each image management device 2 manages the image data of each image and generates the plot information at a present time of each image by combining one or more pieces of plot information generated by one or more of a plurality of plot information generating devices 2. The plotting device 3 receives both the image data and plot information at a present time from the image management device 2 and plots the image data based on the plot information at a present time.

The plot information are generated for each image and includes information about the position coordinates on a screen of an image. When an image is reproduced, each of the plurality of plot information generating device 1 generates plot information for plotting a different movement element, and the image management device 2 generates

one piece of plot information by combining a plurality of pieces of plot information generated by the plurality of plot information generating devices 1.

5 For example, if the first and second plot information generating device generate plot information for indicating the vertical vibration of a sine wave and plot information for indicating the rightward shift, respectively, plot information
10 obtained by combining those pieces of plot information indicates a rightward shift with a vertical vibration along the locus of a sine wave.

 The plotting device 3 plots image data based on the plot information composed in this way and
15 represents a composed movement. If there are a plurality of image management devices 2, the plotting device 3 plots the image data based on plot information corresponding to each piece of image data and combines a plurality of images on a screen.

20 In this way, a complex movement can be easily generated by combining a plurality of pieces of plot information generated by a plurality of plot information generating devices 1, in real time when an image is reproduced. Since the plurality of image
25 management devices 2 can use one plot information

generating device 1, one movement element can be used to plot a plurality of different images.

Alternatively, a plot information generating device 1 can also be handled as a movement component
5 for plotting an individual movement, and a plot information generating device 1 can also be added/deleted according to an event generated while a dynamic image is reproduced. Therefore, the movement of an image can be modified by a user's
10 input operation, etc.

For example, the plot information generating device 1 shown in Fig. 1 corresponds to the plot information generating unit 23 shown in Fig. 2 and the plot information generating unit 41 shown in
15 Fig. 4, which are both described later. The image management device 2 corresponds to the image management unit 11 shown in Fig. 2. The plotting device 3 corresponds to the plotting unit 12, VRAM (video random access memory) 13 and display 14 which
20 are shown in Fig. 2.

According to the present invention, a plurality of plot information generation units are provided for each image component, and the movement of each image component is composed in real time
25 when an image is reproduced. For plot information,

the position, size, rotation angle, color, sequential relationship, etc., of an image component are used, and the movement of each image component can be determined by providing plot information at each time. A complex movement can be easily generated by combining in real time a plurality of pieces of plot information generated by the plurality of plot information generating units. A movement element can be widely used by enabling the same movement element to be referred by a plurality of plot information generating units.

Fig. 2 shows the configuration of a dynamic image composition apparatus based on absolute plot information. The dynamic image composition apparatus shown in Fig. 2 comprises one or more image management units 11, a plotting unit 12, a VRAM 13 and a display 14.

The image management unit 11 is provided for each image component, and, for example, it passes both image data and plot information at a present time to the plotting unit 12 at appropriate intervals, such as once per frame, etc., or at dynamically determined intervals. The plotting unit 12 writes the image data, received from each image management unit 11, in the VRAM 13 based on the plot information

and displays the data on the screen of the display 14.

The image management unit 11 includes an image source 21, a memory 22 and one or more plot information generating units 23. The image source 21 is, for example, a still image memory, a motion picture image decoder, etc., and it generates image data to be written in the VRAM 13. Therefore, the data in the image source 21 include arbitrary images, such as a still image, motion picture image, character, symbol, etc.

The plot information generating units 23 are linked to one another in an order relation. Each plot information generating unit 23 calculates the absolute plot information at a present time according to a corresponding movement element, adds the calculation result at a present time to the plot information passed by a higher-order plot information generating unit 23 and passes the information to a lower-order plot information generating unit 23.

The highest-order plot information generating unit 23 reads the plot information at a previous time from the memory 22, calculates plot information at a present time based on the information and passes

the information to a lower-order plot information generating unit 23. The plot information at a present time outputted by the lowest-order plot information generating unit 23 is passed to the plotting unit 5 12 and is simultaneously written in the memory 22.

In this case, the order, type and number of the plot information generating units can be fixed or can be dynamically changed according to time, by a user's operation, etc. The plot information 10 generating unit 23 can be configured by software or hardware.

The dynamic image composition apparatus shown in Fig. 2 can be implemented, for example, by the configuration shown in Fig. 3. The dynamic image 15 composition apparatus shown in Fig. 3 further comprises a plot information string management unit 31 in addition to the constituent components shown in Fig. 2.

The plot information string management unit 20 31 stores one or more plot information strings 32, and these plot information strings 32 are identified by identifiers (indexes). The plot information string 32 is a list of a plurality of pieces of plot information at arbitrarily discrete times, and it 25 describes respective pieces of plot information at

each time of, for example, 0, 10, 60 and 65 seconds.

Each plot information generating unit 23 stores both an identifier 33 for referring to the plot information string 32 and a modification parameter 34 for modifying plot information. At a specific time, the plot information generating unit 23 extracts two pieces of plot information before and after the time from the plot information string 32 in the plot information string management unit 31 corresponding to the identifier 33. Then, the plot information generating unit 23 calculates plot information at a present time by a method of performing interpolation using the extracted plot information, etc.

Then, the plot information generating unit 23 enlarges or reduces the calculated plot information by the parameter 34, adds the calculation result at a present time to the plot information passed by a higher-order plot information generating unit 23 and passes the information to a lower-order plot information generating unit 23. The parameter 34 can be not only applied to plot information itself, but it can also be applied to a time when the plot information is extracted. By changing a time in this way, the movement speed of an image can be changed.

Fig. 4 shows a dynamic image composition apparatus based on the difference between two pieces of plot information. The dynamic image composition apparatus shown in Fig. 4 comprises one or more image management units 11, a plotting unit 12, a VRAM 13 and a display 14 like the dynamic image composition apparatus shown in Fig. 2.

The image management unit 11 includes an image source 21, a memory 22, one or more plot information generating units 41 and adders 42 and 43. Each plot information generating unit 41 calculates the difference in plot information (difference plot information) between a previous time and a present time according to a corresponding movement element, and adds the difference to the adder 43.

The adder 43 totals a plurality of pieces of the difference plot information at a present time outputted by the plot information generating units 41, and the adder 42 obtains plot information at a present time by adding the totaled difference plot information at a present time to plot information at a previous time read from the memory 22. The plot information at a present time outputted from the adder 42 is passed to the plotting unit 12 and is simultaneously stored in the memory 22.

In this case, the type and number of the plot information generating units 41 can be fixed or can be dynamically changed according to time, by a user's operation, etc. The operational order of the plot information generating units 41 does not have to be specially designated and they can also be operated in parallel. The plot information generating units 41 can be configured by software or hardware.

10 The dynamic image composition apparatus shown in Fig. 4 can be implemented, for example, by a configuration, as shown in Fig. 5.

15 The dynamic image composition apparatus shown in Fig. 5 further comprises the plot information string management unit 31 shown in Fig. 3 in addition to the constituent components shown in Fig. 4.

20 Each plot information generating unit 41 stores both an identifier 33 for referring to the plot information string 32 and a modification parameter 34 for modifying plot information like the plot information generating unit 23 shown in Fig. 3. The plot information generating unit 41 calculates difference plot information at a present time by a method of performing interpolation based on the plot information extracted from the plot

25

information string management unit 31 using the identifier 33, etc. Then, the plot information generating unit 41 enlarges or reduces the calculated difference plot information by the parameter 34 and
5 outputs the calculation result to the adder 43.

Next, the operation of the dynamic image composition apparatus described above is described in detail. Here, a plot process in the case where the image management unit 11 and plotting unit 12
10 are configured by reproduction software is mainly described.

It is assumed that the data of the image source 21, the data of the plot information string management unit 31, the programs of the plot information generating units 23 and 41, the program
15 of the plotting unit 12, etc., are already read and expanded in the memory of a computer. For example, if the image source 21 is an MPEG (Moving Picture Experts Group) decoder, motion picture data after
20 image expansion are read into the memory.

The plotting unit 12 stores a variable in order to receive an event notice from another event control unit, such as an event loop, etc. For the event, an arbitrary form, such as a user's input operation,
25 interruption by the system, etc., and the event is

not limited to a specific form.

Although for the plot update interval, a specific value dt is used, the same fundamental algorithm can be applied even if an update interval is dynamically changed depending on the function of reproduction hardware, etc. Generally, the longer the update interval, the smaller the plotting frequency and the higher the plotting speed. Therefore, a real time process can be implemented by appropriately adjusting an update interval.

Although for plot information, two-dimensional coordinates corresponding to the position at which an image is displayed are used, the same fundamental algorithm can also be applied, even if other plot information, such as the size, rotation angle, etc., of an image is used.

Although for the data included in the plot information string 32, an identifier, time and two-dimensional coordinate string are used, the overall algorithm does not change, even if information indicating a more complex movement is included. Since the plot information generating units 23 and 41 store respective unique internal times and coordinate spaces, different movements

can be represented by one plot information string
32.

Fig. 6 shows a dynamic image composition
process in the case where a plot information function
5 is used instead of the plot information string 32
in the configuration shown in Fig. 3. The plot
information function management unit 51 shown in
Fig. 6 stores one or more plot information functions
52 in the form of a list, and these plot information
10 functions 52 can be identified by identifiers.

The plotting unit 12 stores a list 61 of pointers
to an arbitrary number of image management units
11, a variable 62 for receiving an event notice and
an image update interval 63. A pointer $pImage_i$
15 ($i=1,2,\dots,M$) included in the list 61 indicates an
image management unit # i .

Each image management unit 11 stores the data
64 of the image source 21, the most recent plot
coordinates 65 at a previous time corresponding to
20 the memory 22, the plot coordinates 66 and the
highest-order image information generating unit #1,
and the plot information generating unit # i
($i=1,2,\dots,N-1$) stores pointer lpi to a lower-order
plot information generating unit #(i+1). However,
25 the lowest-order plot information generating unit

#N stores no pointer to another plot information generating unit 23.

Each plot information generating unit #i ($i=1,2,\dots,N$) stores a plot information function identifier pfk ($k=1,2,\dots,K$), a speed parameter speedi, scale parameters x_scalei and y_scalei and an internal time t_lasti.

Since the identifier pfk corresponds to the plot information function 52 of the plot information function management unit 51, each plot information generating unit 23 can refer to an arbitrary information function 52. Therefore, one plot information function 52 can sometimes be referred by a plurality of plot information generating units 23 in one image management unit 11 and can sometimes be referred by the respective plot information generating units 23 in a plurality of image management units 11.

Fig. 7 is a flowchart showing the plot update process of the dynamic image composition apparatus shown in Fig. 6. M pieces of image data 64 of image management units #1-#M are sequentially plotted on coordinates generated via plot information generating units #1-#N by one plot update process. A loop a corresponds to a process of calling up each

y_last) (step S4), and the plotting unit 12 plots the image data 64 at the position of the coordinates (x, y) (step S5).

When the loop a processes of all image management units 11 are completed, the plotting unit 12 clears the variable Event in order to receive a new event notice (step S6) and terminates the process.

Fig. 8 is a flowchart showing the event process in step S2 shown in Fig. 7. The event information stored in the variable Event of the plotting unit 12 includes both the identifier of the image data 64 and a flag indicating that a new plot information generating unit 23 should be generated or that an existing plot information generating unit 23 should be deleted. The event information also includes additional information for designating a plot information generating unit 23 to be generated/deleted.

On receipt of the event information from the plotting unit 12, the image management unit 11 judges from the identifier whether the image data 64 being processed are the target of the event notice (step S11). If the image data 64 being processed are not the target, the image management unit 11 terminates

the process. If the image data are the target, the image management unit 11 adds/deletes a plot information generating unit 23 using both the flag and additional information.

5 Here, the image management unit 11 judges whether the flag indicates the addition of a plot information generating unit (step S12). If it is judged that the flag indicates the addition, the image management unit 11 adds a plot information
10 generating unit 23 designated by the additional information (step S13) and terminates the process. If it is judged that the flag does not indicate the addition, the image management unit 11 deletes a plot information generating unit 23 designated
15 by the additional information (step S14) and terminates the process.

 The addition/deletion of a plot information generating unit 23 can be implemented, for example, by adding data to the list of plot information
20 generating units 23 stored by the image management unit 11 and deleting data from the list. At this time, pointers between plot information generating units 23 are reorganized, if required.

 The complex movement of an image can be
25 dynamically changed by such a dynamic reorganization

process of plot information generating units 23.
 For example, by deleting a plot information
 generating unit 23 only for a single vibration or
 only for a parallel shift from the image management
 5 unit 11 for an image which is obtained by combining
 the single vibration and parallel shift and which
 moves in the form of a sine wave, the present movement
 of the image can be transferred to another simpler
 movement. By adding a plot information generating
 10 unit 23 for single vibration to the image management
 unit 11 of an image which moves in parallel, the
 present movement of the image can be transferred
 to another more complex movement.

Fig. 9 is a flowchart showing the plot
 15 information generating process in step S3 shown in
 Fig. 7. The highest-order plot information
 generating unit #1 executes a process using both
 an update interval dt and plot coordinates (x, y)
 as inputs, and outputs updated plot coordinates $(x,$
 20 $y)$.

The plot information generating unit #1 first
 multiplies the update interval dt by a parameter
 speed1 to convert a global update interval dt to
 the internal update interval $dt1$ of the plot
 25 information generating unit #1 (step S21).

Then, the plot information generating unit #1 obtains a plot information function $f1(t_last, dt, x, y)$ corresponding to a plot information function identifier pfl from the plot information function management unit 51 (step S22). This plot information function obtaining process is described later. Then, the plot information generating unit #1 calculates new plot coordinates (x, y) according to the following equation using an internal time t_last1 calculated at a previous time, the internal update interval $dt1$ and the inputted plot coordinates (x, y) (step S23).

$$(x, y) = f1(t_last1, dt1, x, y) \quad (1)$$

15

Equation (1) indicates that x and y are calculated as functions of t_last1 , $dt1$, x and y . For $f1(t_last1, dt1, x, y)$, for example, a function in which $x=0$, $y=\sin(t_last1+dt1)$, is used.

20

Then, in order to convert the obtained plot coordinates (x, y) from the internal coordinate space to a global coordinate space, x and y are multiplied by a parameter x_scale1 and y_scale1 , respectively, and the results are assigned to x and y , respectively

25 (step S24).

Then, the plot information generating unit #1 updates the internal time by assigning $t_last1 = t_last1 + dt1$ (step S25) and judges whether there is a lower-order plot information generating unit 23 (step S26). In this case, if there is a pointer 1p1 to the lower-order information generating unit 23, it is judged that there is a lower-order plot information generating unit 23. If there is no lower-order plot information generating unit 23, the plot coordinates (x, y) are outputted as the result of one update process.

If there is a lower-order plot information generating unit 23, the plot information generating unit #1 calls up the lower-order plot information generating unit 23, provides the lower-order plot information generating unit 23 with both the update interval dt and obtained plot coordinates (x, y) as inputs and makes the lower-order plot information generating unit 23 execute the same plot information generating process (step S27). In this case, the plot information generating process shown in Fig. 9 is recurrently called up and the process of a plot information generating unit #i is executed.

At this time, the plot information generating unit #i calculates $dt1 = dt * speed_i$ in step S21, obtains

a plot information function $fk(t_last, dt, x, y)$ corresponding to the identifier pfk in step S22 and calculates the plot coordinates (x, y) according to the following equation in step S23.

5

$$(x, y) = fk(t_lasti, dt1, x, y) \quad (2)$$

The plot information generating unit #i calculates $x=x*x_scalei$ and $y=y*y_scalei$ in step
10 S24, calculates $t_lasti=t_lasti+dt1$ in step S25 and judges whether there is a pointer lpi in step S26.

If in step S26 there is a lower-order plot information generating unit 23, the plot information generating unit #i calls up the lower-order plot
15 information generating unit 23. If there is no lower-order plot information generating unit 23, the plot information generating unit #i outputs the obtained plot coordinates (x, y) to the original higher-order plot information generating unit 23
20 and terminates the process.

On receipt of the plot coordinates from the lower-order plot information generating unit 23, the higher-order plot information generating unit 23 sequentially passes the plot coordinates to other
25 higher-order plot information generating units 23

and the highest plot information generating unit #1 outputs the received plot coordinates as the result of one update process.

By such a plot information generating process,
 5 a plurality of plot information generated by a plurality of pieces of plot information generating units 23 can be combined in real time and they can be supplied to the plotting unit 12. Therefore, the complex movement of an image can be easily generated
 10 by automatically repeating the update of the image.

Fig. 10 is a flowchart showing the plot information function obtaining process in step S22 shown in Fig. 9. When the plot information generating unit #i passes the identifier pfk to the plot
 15 information function management unit 51, the plot information function management unit 51 executes the loop a process. Loop a is repeated K times in correspondence with the number of plot information functions.

20 In loop a, the plot information function management unit 51 compares the inputted identifier pfk with the identifier of one plot information function 52 (step S31). If the identifiers match, the plot information function management unit 51
 25 outputs a plot information function 52 corresponding

to the identifier pfk (step S32) and terminates the process. If the identifiers do not match, the plot information function management unit 51 repeats a process of comparing the identifier pfk with the
 5 identifier of a subsequent plot information function 52.

Fig. 11 shows a dynamic image composition process in the case where the configuration shown in Fig. 3 is used. The plot information string management unit 31 shown in Fig. 11 stores one or
 10 more plot information strings 32 in the form of a list, and these plot information strings 32 are identified by identifiers. Each plot information string 32 includes a string of discrete times and
 15 plot coordinate values.

The list 61, event variable 62 and update interval 63 of the plotting unit 12, and the image data 64, last plot coordinates 65 and plot coordinates 66 of the image management unit 11 are
 20 the same as those shown in Fig. 6. Each plot information generating unit #i ($i=1,2,\dots,N$) stores an information string identifier IDk ($k=1,2,\dots,K$) instead of the plot information function identifier shown in Fig. 6.

25 Since the identifier IDk corresponds to the

plot information string 32 of the plot information string management unit 31, each plot information generating unit 23 can refer to an arbitrary plot information string 32. Therefore, one plot information string 32 can sometimes be referred by a plurality of plot information generating units 23 in one image management unit 11 and can sometimes be referred by the respective plot information generating units 23 in a plurality of image management units 11.

The plot information generating unit #i stores a difference calculation flag bDiffi as one of the parameters. The plot information generating unit #i adds a difference to inputted plot coordinates and outputs the coordinates if this bDiffi value is true, and it outputs absolute plot coordinates regardless of inputted plot coordinates if the bDiffi value is false.

The plot update process of the dynamic image composition apparatus shown in Fig. 11 is basically the same as that shown in Fig. 7. However, in step S3 shown in Fig. 7, the highest-order plot information generating unit #1 executes the plot information generating process shown in Fig. 12 using both an update interval dt and plot coordinates (x,

y) as inputs and it outputs the updated plot coordinates (x, y).

The plot information generating unit #1 first converts the update interval dt to an internal update interval $dt1$ by multiplying the update interval dt by a parameter $speed1$ (step S41) and obtains a plot information string corresponding to a plot information string identifier $ID1$ (step S42). This plot information string obtaining process is described later.

Then, the plot information generating unit #1 obtains coordinate values at times before and after t_{last1} and $t_{last1}+dt1$, and calculates the coordinate change difference (dx , dy) between t_{last1} and $t_{last1}+dt1$ by interpolation using those coordinate values (step S43). This difference (dx , dy) corresponds to the movement amount of an image during the internal update interval $dt1$.

For example, if the plot information string shown in Fig. 13 is obtained, the difference (dx , dy) is calculated as follows. However, it is assumed that $t1 < t2 < t3 < \dots < tJ$ is satisfied, $x1$, $x2$, $x3$, ..., xJ are different and $y1$, $y2$, $y3$, ..., yJ are different.

First, in the case of $t1 < t_{last1} < t_{last1}+dt1 < t2$, the difference (dx , dy)

is calculated according to the following equations.

$$\begin{aligned} dx &= (x_2 - x_1) * dt_1 / (t_2 - t_1) \\ dy &= (y_2 - y_1) * dt_1 / (t_2 - t_1) \end{aligned} \quad (3)$$

5

In the case of $t_1 < t_{\text{last1}} < t_2 < \dots < t_j < t_{\text{last1}} + dt_1 < t(j+1)$, the difference (dx, dy) is calculated according to the following equations.

10

$$\begin{aligned} dx &= (x_2 - x_1) * (t_2 - t_{\text{last1}}) / (t_2 - t_1) \\ &\quad + x_j - x_2 \end{aligned}$$

$$+ (x(j+1) - x_j) * (t_{\text{last1}} + dt_1 - t_j) / (t(j+1) - t_j)$$

15

$$dy = (y_2 - y_1) * (t_2 - t_{\text{last1}}) / (t_2 - t_1)$$

(4)

$$+ y_j - y_2$$

$$+ (y(j+1) - y_j) * (t_{\text{last1}} + dt_1 - t_j) / (t(j+1) - t_j)$$

20

In the case of $t_{\text{last1}} < t_J < t_{\text{last1}} + dt_1$, the difference (dx, dy) is calculated according to the following equations.

25

$$dx = (x_J - x(J-1)) * (t_J - t_{\text{last1}}) / (t_J - t(J-1))$$

$$dy = (y_J - y_{(J-1)}) * (t_J - t_{last1}) / (t_J - t_{(J-1)})$$

(5)

In the case of $t_{last1} > t_J$, the difference (dx, dy) is calculated according to the following equations.

$$dx = 0$$

$$dy = 0$$

(6)

10

Although these equations (3), (4), (5) and (6) are an example of linear interpolation, a more complex interpolation method can also be used when a difference (dx, dy) is obtained from plot information string data.

15

After the difference (dx, dy) is obtained, the plot information generating unit #1 multiplies coordinates dx and dy by parameters x_scale1 and y_scale1 , respectively, and assigns the results to coordinates dx and dy, respectively (step S44). Then, the plot information generating unit #1 judges the value of the difference calculation flag bDiff1 (step S45).

20

If the value of the flag bDiff1 is true, the plot information generating unit #1 adds the

25

difference (dx, dy) to inputted plot coordinates (x, y) and assigns the result to the coordinates (x, y) (step S46). If the value of the flag bDiff1 is false, the plot information generating unit #1
 5 assigns the difference (dx, dy) to the coordinates (x, y) with no addition (step S47). In this case, the inputted plot coordinates (x, y) are cancelled and new coordinates (x, y) are generated.

Then, the plot information generating unit #1
 10 updates the internal time by assigning $t_last1 = t_last1 + dt1$ (step S48) and judges whether there is a lower-order plot information generating unit 23 (step S49). If there is no lower-order plot information generating unit 23, the plot information
 15 generating unit #1 outputs the plot coordinates (x, y) as a result of one update process.

If there is a lower-order information generating unit 23, the plot information generating unit #1 calls up the lower-order information
 20 generating unit 23, provides the lower-order information generating unit 23 with both the update interval dt and obtained plot coordinates (x, y) as inputs and makes the lower-order information generating unit 23 execute the same plot information
 25 generating process (step S50). In this case, the

plot information generating process shown in Fig. 12 is recurrently called up and the process of the plot information generating unit #i is executed.

In this case, the plot information generating unit #i calculates $dt1 = dt * speed_i$ in step S41, obtains a plot information string corresponding to the identifier IDk in step S42 and calculates the coordinate change difference (dx, dy) between t_{lasti} and $t_{lasti} + dt1$ based on the plot information string.

The plot information generating unit #i also calculates $x = x * x_scale_i$ and $y = y * y_scale_i$ in step S44, also judges the value of the difference calculation flag bDiffi in step S45, also calculates $t_{lasti} = t_{lasti} + dt1$ in step S48 and judges whether there is a pointer lpi in step S49.

If in step S49 there is a lower-order plot information generating unit 23, the plot information generating unit #i calls up the lower-order plot information generating unit 23. If there is no lower-order plot information generating unit 23, the plot information generating unit #i outputs the plot coordinates (x, y) to the original higher-order plot information generating unit 23 and terminates the process.

On receipt of the plot coordinates from the lower-order plot information generating unit 23, the higher-order plot information generating unit 23 sequentially passes the plot coordinates to another higher-order plot information generating unit 23. The highest-order plot information generating unit #1 outputs the received plot coordinates as a result of one update process. By such a plot information generating process, the plot information generating unit 23 can generate plot information using a plot information string instead of a plot information function.

Fig. 14 is a flowchart showing the plot information string obtaining process in step S42 shown in Fig. 12. When the plot information generating unit #i passes the identifier IDk to the plot information string management unit 31, the plot information string management unit 31 executes a loop a process. Loop a is repeated K times corresponding to the number of the plot information strings 32.

In loop a, the plot information string management unit 31 compares the inputted identifier IDk with the identifier of one plot information string 32 (step S51). If the identifiers match, the

plot information string management unit 31 outputs a plot information string 32 corresponding to the identifier IDk (step S52), and terminates the process. If the identifiers do not match, the plot information string management unit 31 repeats the process of comparing the identifier IDk with the identifier of a subsequent plot information string 32.

According to the dynamic image composition apparatus shown in Figs. 6 and 11, each plot information generating unit 23 can cancel plot information passed from a higher-order plot information generating unit 23 and can generate a new piece of plot information. Therefore, for example, the movement of an image can also be stopped at a specific predetermined time.

Generally, if each plot information generating unit 23 generates absolute plot information using the plot information from a higher-order plot information generating unit 23 as an input, plot information outputted from the image management unit 11 is affected by the operation order of the plot information generating unit 23.

For example, a case is considered where the image management unit 11 includes two plot

information generating units #1 and #2, the plot
 information generating unit #1 generates the plot
 information about a vertical vibration on a screen
 and the plot information generating unit #2 generates
 5 plot information which moves rightward between time
 0 and time t_1 and stops at time t_1 .

In this case, the plot information generating
 units #1 and #2 are operated in that order. Lastly,
 plot information of an image which moves rightward
 10 while vertically vibrating between times 0 and t_1
 and stops there at and after time t_1 , is outputted.
 If the plot information generating units #2 and #1
 are operated in that order, lastly, plot information
 of an image which moves rightward while vertically
 15 vibrating between times 0 and t_1 and it vertically
 vibrates there at and after time t_1 , is outputted.
 Therefore, the composition movement differs
 depending on the operation order of the plot
 information generating units #1 and #2.

20 Fig. 15 shows the dynamic image composition
 process in the case where a plot information function
 52 is used instead of a plot information string 32
 in the configuration shown in Fig. 5. The pointer
 list 61, event variable 62 and update interval 63
 25 of the plotting unit 12; the image data 64, last

plot coordinates 65 and plot coordinates 66 of the
 image management unit 11; information stored in the
 plot information generating units 41; and the plot
 information function management 51 which are all
 5 shown in Fig. 15 are the same as those shown in Fig.
 6.

Each image management unit 11 also stores
 difference coordinates 67 and further stores one
 or more plot information generating units 41 in the
 10 form of a list.

Fig. 16 is a flowchart showing the plot update
 process of the dynamic image composition apparatus
 shown in Fig. 15. By one plot update process, M pieces
 of image data of the image management units #1-#M
 15 are sequentially plotted on coordinates generated
 by the plot information generating units #1-#N. A
 loop a corresponds to a process of calling up each
 image management unit 11 and is repeated M times.
 A loop b corresponds to a process of calling up each
 20 plot information generating unit 41 and is repeated
 N times.

In loop a, the image management unit 11 executes
 the event process shown in Fig. 8 (step S61), assigns
 the last plot coordinates (x_{last} , y_{last}) at a
 25 previous time to plot coordinates (x , y) (step S62)

and executes the process of loop b.

In loop b, the plot information generating unit 41 is called up, and coordinate change difference (dx, dy) during an update interval dt is calculated (step S63). The details of this plot information generating process are described later. Then, the obtained difference (dx, dy) is added to the plot coordinates (x, y), and the result is assigned to the plot coordinates (x, y) (step S64).

As for loop b, lower-order plot information generating units #(i+1) can be sequentially called up tracing a pointer lpi from the highest-order plot information generating unit #1 or the plot information generating units #1-#N can be operated in parallel.

After the loop b processes of all plot information generating units 41 are completed, the image management unit 11 assigns the obtained coordinates (x, y) to coordinates (x_last, y_last) (step S65), and the plotting unit 12 plots the image data 64 at the position of the plot coordinates (x, y) (step S66).

After the loop a processes of all image management units 11 are completed, the plotting unit 12 clears the variable Event to receive a new event

notice (step S67) and terminates the process.

Fig. 17 is a flowchart showing the plot information generating process in step S63 shown in Fig. 16. The plot information generating unit #i executes a process using an update interval dt as an input and outputs a plot coordinate difference (dx, dy).

The plot information generating unit #i first multiplies the update interval dt by a parameter speedi and converts the update interval dt to an internal update interval dt1 (step S71). Then, the plot information generating unit #i obtains a plot information function fk(t) corresponding to a plot information function identifier pfk from the plot information function management unit 51 by executing the plot information function obtaining process shown in Fig. 10 (step S72). Here, it is assumed that fk(t) is expressed by the following equation.

$$fk(t) = (fkx(t), fky(t)) \quad (7)$$

The plot information generating unit #i calculates the difference (dx, dy) according to the following equation using both an internal time t_last1 calculated at a previous time and the internal update

interval $dt1$ (step S73).

$$\begin{aligned} dx &= f_{kx}(t_{lasti} + dt1) - f_{kx}(t_{lasti}) \\ 5 \quad dy &= f_{ky}(t_{lasti} + dt1) - f_{ky}(t_{lasti}) \end{aligned} \quad (8)$$

Equation (8) indicates the respective differences of functions $f_{kx}(t)$ and $f_{ky}(t)$ between
10 internal times t_{lasti} and $t_{lasti} + dt1$.

Then, the plot information generating unit # i multiplies the obtained differences (dx, dy) by parameters x_scalei and y_scalei , respectively, and the results are assigned to the differences dx and
15 dy , respectively (step S74). Then, the plot information generating unit # i updates the internal time by assigning $t_{lasti} = t_{lasti} + dt1$ (step S75), outputs the difference (dx, dy) and terminates the process.

20 The difference (dx, dy) outputted by each plot information generating unit # i is added to the plot coordinates (x, y) in step S64 shown in Fig. 16 and lastly the plot coordinates (x, y) are updated by the sum of differences (dx, dy) outputted by all
25 plot information generating units 41.

By such a plot information generating process,
a plurality of pieces of plot information generated
by a plurality of plot information generating units
41 can be combined in real time when an image is
5 updated and they can be provided to the plotting
unit 12. Therefore, the complex movement of an image
can be easily generated by automatically repeating
the update of the image.

Fig. 18 shows the dynamic image composition
10 process in the case of the configuration shown in
Fig. 5. The pointer list 61, event variable 62 and
update interval 63 of the plotting unit 12; and the
image data 64, last plot coordinates 65, plot
coordinates 66 and difference coordinates 67 of the
15 image management unit 11 shown in Fig. 18 are the
same as those shown in Fig. 15. Both pieces of
information stored in the plot information
generating unit 41 and the plot information string
management unit 31 are the same as those shown in
20 Fig. 11. However, the plot information generating
unit 41 does not store a difference calculation flag.

The plot update process of the dynamic image
composition apparatus shown in Fig. 18 is basically
the same as that shown in Fig. 16. However, in step
25 S63 shown in Fig. 16, the plot information generating

unit 41 executes the plot information generating process shown in Fig. 19 using an update interval dt as an input and outputs plot coordinate difference (dx, dy) .

5 The plot information generating unit # i first multiplies the update interval dt by a parameter $speed_i$, converts the update interval dt to an internal update interval $dt1$ (step S81) and obtains a plot information string corresponding to a plot
10 information identifier ID_k from the plot information string management unit 31 by executing the plot information string obtaining process shown in Fig. 14 (step S82).

 Then, the plot information generating unit # i
15 obtains coordinate values at times before and after t_{lasti} and $t_{lasti}+dt1$ from the plot information string and calculates the coordinate change difference (dx, dy) between t_{lasti} and $t_{lasti}+dt1$ by performing interpolation using these coordinate
20 values (step S83).

 Then, the plot information generating unit # i multiplies the obtained differences dx and dy by parameters x_scale_i and y_scale_i , respectively, and assigns the results to the differences dx and dy
25 (step S84). Then, the plot information generating

unit #i updates an internal time by assigning
 $t_lasti = t_lasti + dt1$ (step S85), outputs a
 difference (dx, dy) and terminates the process. By
 such a plot information generating process, the plot
 5 information generating unit 41 can generate plot
 information using a plot information string instead
 of a plot information function.

Although in the preferred embodiments
 described above, the pointer 61 to the image
 10 management unit 11, plot information generating
 units 23 and 41, plot information function 52 and
 plot information string 32 are stored in the form
 of a list, these can be stored in an arbitrary form
 only if it is a structure where an element can be
 15 added/deleted.

Next, the specific example of dynamic image
 composition is described with reference to Figs.
 20 through 23.

Fig. 20 shows a screen structure at time $t=0$.
 20 On this screen, an xy coordinate system having the
 upper left corner as an origin is established and
 three images I1, I2 and I3 are plotted in a state
 where a plot position (x, y) is changed as time
 elapses.

25 Fig. 21 shows the dynamic image composition

process by image management units 11 for managing these images. In this example, the dynamic image composition apparatus shown in Fig. 5 is used and both a plot information function 52 and a plot information string 32 are used.

The image management unit 11 of image I1 stores image data 64, the most recent plot coordinates (x1, y1) and two plot information generating units #1 and #2, the image management unit 11 of image I2 stores image data 64, the most recent plot coordinates (x2, y2) and one plot information generating unit 41, and the image management unit 11 of image I3 stores image data 64, the most recent plot coordinates (x3, y3) and one plot information generating unit 41.

The plot information generating unit #1 of image I1 stores a plot information function identifier pf1, and the plot information generating unit #2 stores a plot information function identifier pf2. The plot information generating unit 41 of image I2 stores a plot information function identifier pf2, and the plot information generating unit 41 of image I3 stores a plot information string identifier ID1.

Each plot information generating unit 41

calculates a position coordinate difference (dx, dy) using an update interval dt to be inputted and a stored last update time t_lasti and using a designated plot information function 52 or plot information string 32. In this example, the difference (dx, dy) is directly provided by each plot information function 52 and it is defined as follows.

```

10      -Plot information function pfl

      dx=0

      dy=100*(sin(t_last+dt)-sin(t_last))      (9)

```

According to this function, an x-direction difference dx is 0 and a y-direction difference dy is equal to 100 times the difference of sin(t) between times t_last and t_last+dt. As a result, this function indicates a vertical vibration with an amplitude of 100.

```

20      -Plot information function pf2

      dx=10*dt

      dy=0                                          (10)

```

25 According to this function, an x-direction

difference dx is equal to ten times the update interval dt and a y -direction difference is 0. As a result, this function indicates a linear shift which is made by 10 shifts per unit time in the

5 x -direction (rightward).

The plot information string 32 includes position coordinates for the four vertices of a square with each side of 100, and a locus designated by the plot information string 32 indicates a

10 clockwise shift along the four sides of the square with an upper left vertex as a start point. In this case, the difference (dx, dy) is calculated based on the designated locus by performing a linear interpolation.

15 Each image management unit 11 calculates position coordinates (x, y) as follows using the difference (dx, dy) calculated by these plot information functions 52 or plot information strings 32.

20 -Image management unit 11 of image I1

The plot information generating unit #1 calculates the difference of a vertical vibration using a plot information function $pf1$ and the plot information generating unit #2 calculates the

25 difference of a rightward shift using a plot

information function pf2. The sum of these two differences becomes the change amount of position coordinates in one update. As a result, image I1 moves along the locus of a sine wave.

5 -Image management unit 11 of image I2

The plot information generating unit 41 calculates the difference of a rightward shift using a plot information function pf2 and the difference becomes the change amount of position coordinates
10 in one update. As a result, image I2 linearly moves rightward.

-Image management unit 11 of image I3

The plot information generating unit 41 calculates the difference of a shift along a square
15 using a plot information string ID1, and the difference becomes the change amount of position coordinates in one update. As a result, image I3 moves along a locus designated by the plot information string ID1.

20 Here, a case is considered where in such a dynamic image composition process, notification of a specific event is posted at time $t=1$ and an event process is executed. In this case, at time $t=0$, each image is plotted in the initial position, as shown
25 in Fig. 20. Between times $t=0$ and $t=1$, each image

moves according to a difference generated by each plot information generating unit 41 and added to the position coordinates, as shown in Fig. 22. Therefore, image I1 moves along the locus of a sine wave, image I2 linearly moves rightward and image I3 moves along the locus of a square.

Then, it is assumed that at time $t=1$, notification of an event is posted and the plot information generating unit #1 is requested by the image management unit 11 of image I1 to be deleted. In this case, the image management unit 11 of image I1 performs an event process, and the image information generating unit #1 is deleted. Therefore, after this, the difference of a vertical vibration is not generated, and only the plot information generating unit #2 generates differences.

Then, between times $t=1$ and $t=2$, each image continues to move according to a difference generated by each plot information generating unit 41 and added to the position coordinates, as shown in Fig. 23. At this time, image I1 stops vertically vibrating, and at time $t=1$, it linearly moves rightward while maintaining the y coordinate value. Image I2 linearly moves rightward and image I3 moves along the locus

of a square.

If the content of the event notification at time $t=1$ is a request to add a new plot information generating unit #3 to the image management unit 11 of image I1, the image management unit 11 adds the plot information generating unit #3. After this, differences generated by three plot information generating units #1, #2 and #3 are added and the position coordinates of image I1 is determined.

By the way, the dynamic image composition apparatuses shown in Figs. 6, 11, 15 and 18 can be configured using an information processing device (computer) shown in Fig. 24. The information processing device shown in Fig. 24 comprises a CPU (central processing unit) 71, a memory 72, an input device 73, an output device 74, an external storage device 75, a medium driving device 76 and a network connection device 77, which are connected to one another by a bus 78.

The memory 72 includes, for example, a ROM (read only memory), RAM (random access memory), etc., and it stores a program and data used for the process. The CPU 71 performs necessary processes by using the memory 72 and executing the program.

In these examples, the image management unit

11, plotting unit 12, image information function management unit 51, image information string management unit 31, image information generating units 23 and 41, etc., correspond to software components described by the program, and each component is stored in the specific program code segment of the memory 72. The list of pointers 61, event variable 62, update interval 63, image data 64, last plot coordinates 65, other plot coordinates 66, etc., are also stored in the memory 72.

The input device 73 includes, for example, a keyboard, a pointing device, touch panel, etc., and it is used to input a user's instruction and information. Notification of an input operation to the input device 73 is also sometimes made to the plotting unit 12 as an event. The output device 74 includes, for example, the VRAM 13 and display 14 shown in Fig. 5, and it is used to output both inquiries to a user and composed dynamic images.

The external storage device 75 includes, for example, a magnetic disk device, optical disk device, magneto-optical disk device, etc. This external storage device 75 can also store the program and data described above, and the program and data can be used by being loaded into the memory 72, if required.

The external storage device 75 can also be used as a database for storing the image data 64, plot information function 52, plot information string 32, etc.

5 The medium driving device 76 drives a portable storage medium 79 and accesses the recorded content. For the portable storage medium, an arbitrary computer readable storage medium, such as a memory card, floppy disk, CD-ROM (compact disk read only
10 memory), optical disk, magneto-optical disk, etc., is used. The program and data described above can also be stored in this portable storage medium 79, and can also be used by being loaded into the memory 72, if required.

15 The network connection device 77 communicates with external devices via an arbitrary network (line), such as a LAN (local area network), etc., and transmits/receives data accompanying the communications. The connection network device can
20 also receive the program and data from an external device and the program and data can be used by being loaded
into the memory 72, if required.

Fig. 25 shows examples of computer readable
25 storage media which can provide the information

processing device shown in Fig. 24 with the program and data. The program and data stored in the portable storage medium 79 or an external database 80 can be loaded into the memory 72. The CPU 71 executes
5 necessary processes by using the data and running the program.

Although in the preferred embodiments described above, configurations for implementing the image management unit 11 by software have been
10 described, the image management unit 11 can also be implemented by hardware.

Fig. 26 shows a case where a plurality of image management units 11 are configured by one hardware circuit. The image management unit shown in Fig.
15 26 comprises a plurality of memories 81 (#1-#M), selectors 82 and 83 for selecting a memory 81, a plurality of plot information generating circuits 84 (#1-#N), selectors 85 and 86 for selecting a plot information generating circuit 84 and a control
20 circuit 87.

The control circuit 87 switches between the selectors 82 and 83 by a control signal C1, switches between the selectors 85 and 86 by a control signal C2 and controls the plot information generating
25 circuits 84 by a control signal C3. In this example,

it is assumed for simplification purposes that only coordinates (x, y) are handled as plot information.

The memories #1-#M correspond to the image management units #1-#M, respectively, described above and they store plot information obtained at a previous time at time t . The plot information generating circuits #1-#N correspond to the plot information generating units #1-#N, respectively, and are described above and perform a calculation corresponding to one movement element and output the plot information. If the time t , an update interval dt and plot coordinates (x, y) at the previous time are used as input, outputted plot coordinates (x', y') are expressed as follows.

15

$$\begin{aligned} x' &= fx(t, dt, x, y) \\ y' &= fy(t, dt, x, y) \end{aligned} \quad (11)$$

Above, dt corresponds to the difference between the previous time and the present time t , and $fx(t, dt, x, y)$ and $fy(t, dt, x, y)$ correspond to functions to generate an image movement. For example, if a vertical vibration is generated using $\sin(t)$, the following equations hold true.

25

$$\begin{aligned} f_x(t, dt, x, y) &= x \\ f_y(t, dt, x, y) &= y + \sin(t) - \sin(t-dt) \quad (12) \end{aligned}$$

These functions can also output the history
 5 of past plot coordinates. For example, input
 coordinates (x_{t1}, y_{t1}) at time $t1$ can be stored,
 and a function to continue to output the coordinates
 (x_{t1}, y_{t1}) after time $t1$ can be defined.

If the same plot information generating
 10 circuit 84 is used for a plurality of images, such
 plot coordinate data are stored in a register of
 the plot information generating circuit 84 for each
 image, and appropriate data are outputted by
 switching the register by a control signal C3 from
 15 the control circuit 87.

When a plot update process is started at time
 t , first the selectors 82 and 83 are switched over
 by a control signal C1 from the control circuit 87
 and a memory #1 is selected. Then, the selectors
 20 85 and 86 are switched over by a control signal C2
 and a plot information generating circuit #1 is
 selected. Simultaneously, the register of the plot
 information generating circuit #1 is switched by
 a control signal C3, if required, and appropriate
 25 data are selected. In this way, the plot coordinates

of the memory #1 are inputted to the plot information generating circuit #1, and the output from the plot information generating circuit #1 is stored in the memory #1.

5 Then, the selectors 85 and 86 are switched over, a plot information generating circuit #2 is selected and the plot information is inputted from the memory #1 to the plot information generating circuit #2. Then, plot coordinates are generated in the plot
10 information generating circuit #2 in the same way as in the case of the plot information generating circuit #1, and the plot coordinates are stored in the memory #1. After such an operation is repeated for all plot information generating circuits 84
15 assigned to the image management unit #1, the output of the last plot information generating circuit 84 is outputted as the plot information at the present time of the image management unit #1. At this time, the plot information is simultaneously stored in
20 the memory #1.

 After the operation of the image management unit #1 is completed in this way, the selectors 82 and 83 are switched over, the memory #2 is selected and the operation of the image management unit #2
25 is performed in the same way. After such an operation

is repeated for M image management units, the plot update process at time t is completed.

For example, a case is described where the image management unit #1 corresponding to the memory #1
 5 generates a rightward shift along the locus of a sine wave and the image management unit #2 corresponding to a memory #2 generates a leftward shift along the locus of a sine wave. It is assumed that plot information generating circuits #1, #2
 10 and #3 generate the following respective movements.

Plot information generating circuit #1:
 Vertical vibration of $\sin(t)$

Plot information generating circuit #2:
 Rightward linear shift

15 Plot information generating circuit #3:
 Leftward linear shift

In this case, the circuit shown in Fig. 26 first selects a memory #1 using the selectors 82 and 83, and it selects a plot information generating circuit
 20 #1 using the selectors 85 and 86. In this way, the vertical vibration of $\sin(t)$ is added to the coordinates of the memory #1. Then, the circuit selects a plot information generating circuit #2 using the selectors 85 and 86. In this way, a rightward
 25 shift is added to the plot coordinates of a memory

#1, and, as a result, plot coordinates in the case where the plot coordinates move rightward along the locus of a sine wave are outputted.

Then, the circuit selects a memory #2 using
5 the selectors 82 and 83 and it selects the plot
information generating circuit #1 using the
selectors 85 and 86. In this way, the vertical
vibration of $\sin(t)$ is added to the plot coordinates
of the memory #2. Then, the circuit selects a plot
10 information generating circuit #3 using the
selectors 85 and 86. In this way, a leftward shift
is added to the coordinates of the memory #2, and,
as a result, plot coordinates in the case where the
plot coordinates move leftward along the locus of
15 a sine wave are outputted.

In this way, by switching both the memories
81 and plot information generating circuits 84 using
selectors, the outputs of a plurality of plot
information generating circuits 84 can be combined
20 and one image movement can be generated. One plot
information generating circuit 84 can also be used
to generate a plurality of image movements.

As described above, the present invention is
applicable to an arbitrary field, software or
25 hardware, where a dynamic image moves as time elapses

or according to an event. The following are potential software applications.

(1) Dynamic image generation software

(2) Home page generation software and browser
5 software

(3) CD-ROM content generation software and reproduction software

(4) Presentation generation software and reproduction software

10 (5) Game generation software and game software

For example, in a conventional multimedia title generation/reproduction system used for home page generation, etc., only one movement can be given to one image element. Therefore, if a vertical
15 vibration with a rightward shift is given, the combined result of the two movements must be anticipated and prepared in advance.

However, according to the system of the present invention, a vertical vibration with a rightward
20 shift can be composed by separately generating a rightward shift and a vertical shift and by linking both to one image component when an image is reproduced. If this system is adopted, a movement can be dynamically added /deleted according to a
25 user's instruction or time.

According to this system, since a rightward shift and a vertical vibration are separately managed when an image is reproduced, a movement in which the image starts moving rightward while vertically vibrating when the image which is moving rightward is clicked, and in which the image stops vertically vibrating when the image is clicked again, can be easily generated. In this case, the system can be configured in such a way that first a rightward shift is linked to an image component as a fundamental movement and a vertical vibration is added/deleted by a click event. According to the conventional system, a rightward shift and a rightward shift with a vertical vibration are separately configured and they are switched over by a click. However, if the two movements are prepared without concern to the continuity, there is a possibility that the two movements may be discontinued when they are switched over.

If the system of the present invention is adopted, a multimedia title producer can handle each movement as a component. Since each kind of movement element is recorded in the completed multimedia title in a disassembled state, another producer can extract his/her favorite movement element from the

multimedia title and can use the element as a movement component.

For example, it can be considered that a multimedia title including an image which moves along a specific path while vertically vibrating in a specific frequency includes two movement components, that is, a vertical vibration with a frequency and a shift along a path. In this case, the vertical vibration with a frequency can be implemented even in another multimedia title by extracting and using only the vertical vibration with the frequency. However, according to the conventional system, since a movement is composed in advance when the multimedia title is produced, it is very difficult to extract only the vertical vibration with a frequency.

Although in the preferred embodiments described above, for a plot information function, the vertical vibration of a sine wave and a leftward/rightward linear shift are used, another arbitrary function can also be used. For example, the vibration of a cosine wave, a shift along a straight line $y=ax+b$, a shift along a parabola, a shift along a circle/ellipse and the like can also be defined as a function. A plot information string is not limited to the locus of a square, and the

locus of an arbitrary shape, such as a parabola, circle, ellipse, etc., can also be used for a plot information string.

Furthermore, plot information generated by a
5 plot information generating unit is not limited to the plot position of an image and it can also be the enlargement/reduction ratio, rotation angle, color, sequential relationship, etc., of an image component. A more complex dynamic image can be
10 displayed by dynamically combining these pieces of information.

According to the present invention, when a plurality of dynamic images are displayed on a screen, a complex movement can be easily generated by
15 combining a plurality of movement elements. For example, a movement can be added/deleted in real time according to an event, a movement can be stopped or one movement element can be applied to a plurality of images.

What is claimed is:

1. A dynamic image composition apparatus for
combining and plotting one or more images,
5 comprising:

a plurality of plot information generating
devices generating plot information used to plot
a dynamic image;

an image management device managing image data
10 of each image and generating plot information at
a present time of each image by combining one or
more pieces of information generated by one or more
of the plurality of the plot information generating
devices; and

15 a plotting device receiving the image data and
the plot information at the present time from the
image management device and plotting the image data
based on the plot information at the present time.

20 2. The dynamic image composition apparatus
according to claim 1, wherein

said plot information generating device
generates absolute plot information.

25 3. The dynamic image composition apparatus

according to claim 1, wherein

said plot information generating device generates a difference of plot information between a previous time and the present time.

5

4. The dynamic image composition apparatus according to claim 1, further comprising

a plot information function management device storing one or more plot information functions,
10 wherein

at least one of said plurality of said plot information generating devices store identification information for referring to a plot information function and calculates the plot
15 information using the plot information function corresponding to the identification information.

5. The dynamic image composition apparatus according to claim 1, further comprising

20 a plot information string management device storing one or more plot information strings including discrete plot information,
wherein

at least one of said plurality of said plot
25 information generating devices store

identification information for referring to a plot information string and calculates the plot information using the plot information string corresponding to the identification information.

5

6. The dynamic image composition apparatus according to claim 5, wherein

said at least one of said plurality of said plot information generating devices calculate the plot information by performing interpolation using the discrete plot information included in the plot information string.

7. The dynamic image composition apparatus according to claim 1, wherein

said plot information generating device stores a parameter for modifying plot information and calculates the plot information using the parameter.

8. The dynamic image composition apparatus according to claim 1, wherein

said plot information generating device generates as the plot information information about a plot position on a screen of an image.

25

9. A dynamic image composition apparatus for combining and plotting one or more images, comprising:

an image management device provided for each
5 image, for including a plurality of sequentially
ordered plot information generating devices for
generating plot information used to plot a dynamic
image, a first plot information generating device
updating plot information at a previous time and
10 passing the plot information to a subsequent plot
information generating device, an intermediate plot
information generating device updating plot
information provided by a preceding plot information
generating device and passing the plot information
15 to a subsequent plot information generating device,
and a last plot information generating device
updating plot information provided by a preceding
plot information generating device and generating
plot information at a present time; and
20 a plotting device for receiving the plot
information at the present time from the image
management device and plotting a corresponding image
based on the plot information at the present time.

25 10. The dynamic image composition apparatus

according to claim 9, wherein

each plot information generating device generates a difference of plot information between the previous time and the present time, adds the difference to inputted plot information and updates the inputted plot information.

11. A dynamic image composition apparatus for combining and plotting one or more images, comprising:

an image management device provided for each image, for including a plurality of plot information generating devices for generating a difference of plot information used to plot a dynamic image between a previous time and a present time and device for generating plot information at the present time using a sum of differences generated by the plurality of the plot information generating devices; and

plotting device for receiving the plot information at the present time from the image management device and plotting a corresponding image based on the plot information at the present time.

12. A dynamic image composition apparatus for combining and plotting one or more images,

comprising:

a plurality of plot information generating devices for generating information about a plot position in correspondence with a movement element
 5 which generates a movement of a dynamic image on a screen;

an image management device for managing image data of each image and generates information about a plot position at a present time of each image by
 10 combining one or more pieces of information generated by one or more of the plurality of the plot information generating devices; and

a plotting device for receiving the image data and the information about the plot position at the
 15 present time from the image management device and plotting image data based on the information about the plot position at the present time.

13. A computer-readable storage medium on which is
 20 recorded a program for enabling a computer to execute a process, the process comprising:

generating a plurality of pieces of plot information used to plot an image, for each image;

generating plot information at a present time
 25 of each image by combining the plurality of pieces

of plot information ; and

plotting each image based on the plot
information at the present time.

- 5 14. A computer-readable storage medium on which is
recorded a program for enabling a computer to execute
a process, the process comprising:

generating plot information at a present time
by updating plot information used to plot an image
10 at a previous time for each image by a plurality
of sequentially ordered plot information generating
processes; and

plotting each image based on the plot
information at the present time.

15

15. A computer-readable storage medium on which is
recorded a program for enabling a computer to execute
a process, the process comprising:

generating differences of a plurality of
20 pieces of plot information used to plot an image
between a previous time and a present time, for each
image;

generating plot information at the present
time of each image using a sum of the differences
25 of the plurality of the pieces of the plot

information; and

plotting each image based on the plot information at the present time.

- 5 16. A dynamic image composition method for combining and plotting one or more images, comprising:

generating a plurality of pieces of plot information used to plot an image, for each image;

- 10 generating plot information at a present time of each image by combining the plurality of pieces of plot information; and

plotting each image based on the plot information at the present time.

- 15 17. A dynamic image composition apparatus for combining and plotting one or more images, comprising:

a plurality of plot information generating means for generating plot information used to plot

- 20 a dynamic image;

image management means for managing image data of each image and generating plot information at a present time of each image by combining one or more pieces of information generated by one or more

- 25 of the plurality of the plot information generating

means; and

plotting means for receiving the image data
and the plot information at the present time from
the image management means and plotting the image
5 data based on the plot information at the present
time.

18. A dynamic image composition apparatus for
combining and plotting one or more images,
10 comprising:

image management means provided for each image,
for including a plurality of sequentially ordered
plot information generating means for generating
plot information used to plot a dynamic image, a
15 first plot information generating means updating
plot information at a previous time and passing the
plot information to a subsequent plot information
generating means, an intermediate plot information
generating means updating plot information provided
20 by a preceding plot information generating means
and passing the plot information to a subsequent
plot information generating means, and a last plot
information generating means updating plot
information provided by a preceding plot
25 information generating means and generating plot

information at a present time; and

plotting means for receiving the plot
information at the present time from the image
management means and plotting a corresponding image
5 based on the plot information at the present time.

19. A dynamic image composition apparatus for
combining and plotting one or more images,
comprising:

10 image management means provided for each image,
for including a plurality of plot information
generating means for generating a difference of plot
information used to plot a dynamic image between
a previous time and a present time and means for
15 generating plot information at the present time using
a sum of differences generated by the plurality of
the plot information generating means; and

plotting means for receiving the plot
information at the present time from the image
20 management means and plotting a corresponding image
based on the plot information at the present time.

Abstract of the Disclosure

The movement of an image component is determined using the plot information, such as the position, size of the image component, etc., at each time. The complex movement of each image component can be easily generated by providing a plurality of plot information generating units for each image component and combining a plurality of pieces of plot information generated by the plot information generating units when an image is reproduced.

2003 08 06




FIG. 1




FIG. 2




FIG. 3

64534960




FIG. 4

2025 RELEASE UNDER E.O. 14176




FIG. 5




FIG. 6




FIG. 7

006260" 64052960




FIG. 8

000250" 61252350





FIG. 9

```

graph TD
    Start([START  
INPUTS AN IDENTIFIER pfk]) --> LoopA1[/LOOP a  
REPEATED BY THE  
NUMBER OF PLOT  
INFORMATION FUNCTIONS/]
    LoopA1 --> S31{S31  
DO pfk AND THE  
IDENTIFIER OF A  
PLOT INFORMATION  
FUNCTION MATCH?}
    S31 -- Y --> S32[DESIGNATES THE  
DESIGNATED NUMBER IF  
PLOT INFORMATION  
FUNCTIONS AS AN OUTPUT]
    S31 -- N --> LoopA2[/LOOP a/]
    S32 --> LoopA2
    LoopA2 --> End([END  
OUTPUTS A PLOT INFORMATION  
FUNCTION])
  
```

FIG. 10



006250 64054 850




FIG. 12

000000 01052900

TIME	X COORDINATE	Y COORDINATE
t 1	x 1	y 1
t 2	x 2	y 2
t 3	x 3	y 3
...
t J	x J	y J

F I G. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18

[illegible]

- S81

S82

S83

S84

S85

FIG. 19

FIG. 19


[illegible]

FIG. 20




FIG. 21




FIG. 22

000260 0105/360




FIG. 23

1997-1998
1998-1999
1999-2000
2000-2001
2001-2002
2002-2003
2003-2004
2004-2005
2005-2006
2006-2007
2007-2008
2008-2009
2009-2010
2010-2011
2011-2012
2012-2013
2013-2014
2014-2015
2015-2016
2016-2017
2017-2018
2018-2019
2019-2020
2020-2021
2021-2022
2022-2023
2023-2024
2024-2025
2025-2026
2026-2027
2027-2028
2028-2029
2029-2030
2030-2031
2031-2032
2032-2033
2033-2034
2034-2035
2035-2036
2036-2037
2037-2038
2038-2039
2039-2040
2040-2041
2041-2042
2042-2043
2043-2044
2044-2045
2045-2046
2046-2047
2047-2048
2048-2049
2049-2050
2050-2051
2051-2052
2052-2053
2053-2054
2054-2055
2055-2056
2056-2057
2057-2058
2058-2059
2059-2060
2060-2061
2061-2062
2062-2063
2063-2064
2064-2065
2065-2066
2066-2067
2067-2068
2068-2069
2069-2070
2070-2071
2071-2072
2072-2073
2073-2074
2074-2075
2075-2076
2076-2077
2077-2078
2078-2079
2079-2080
2080-2081
2081-2082
2082-2083
2083-2084
2084-2085
2085-2086
2086-2087
2087-2088
2088-2089
2089-2090
2090-2091
2091-2092
2092-2093
2093-2094
2094-2095
2095-2096
2096-2097
2097-2098
2098-2099
2099-2100
2100-2101
2101-2102
2102-2103
2103-2104
2104-2105
2105-2106
2106-2107
2107-2108
2108-2109
2109-2110
2110-2111
2111-2112
2112-2113
2113-2114
2114-2115
2115-2116
2116-2117
2117-2118
2118-2119
2119-2120
2120-2121
2121-2122
2122-2123
2123-2124
2124-2125
2125-2126
2126-2127
2127-2128
2128-2129
2129-2130
2130-2131
2131-2132
2132-2133
2133-2134
2134-2135
2135-2136
2136-2137
2137-2138
2138-2139
2139-2140
2140-2141
2141-2142
2142-2143
2143-2144
2144-2145
2145-2146
2146-2147
2147-2148
2148-2149
2149-2150
2150-2151
2151-2152
2152-2153
2153-2154
2154-2155
2155-2156
2156-2157
2157-2158
2158-2159
2159-2160
2160-2161
2161-2162
2162-2163
2163-2164
2164-2165
2165-2166
2166-2167
2167-2168
2168-2169
2169-2170
2170-2171
2171-2172
2172-2173
2173-2174
2174-2175
2175-2176
2176-2177
2177-2178
2178-2179
2179-2180
2180-2181
2181-2182
2182-2183
2183-2184
2184-2185
2185-2186
2186-2187
2187-2188
2188-2189
2189-2190
2190-2191
2191-2192
2192-2193
2193-2194
2194-2195
2195-2196
2196-2197
2197-2198
2198-2199
2199-2200
2200-2201
2201-2202
2202-2203
2203-2204
2204-2205
2205-2206
2206-2207
2207-2208
2208-2209
2209-2210
2210-2211
2211-2212
2212-2213
2213-2214
2214-2215
2215-2216
2216-2217
2217-2218
2218-2219
2219-2220
2220-2221
2221-2222
2222-2223
2223-2224
2224-2225
2225-2226
2226-2227
2227-2228
2228-2229
2229-2230
2230-2231
2231-2232
2232-2233
2233-2234
2234-2235
2235-2236
2236-2237
2237-2238
2238-2239
2239-2240
2240-2241
2241-2242
2242-2243
2243-2244
2244-2245
2245-2246
2246-2247
2247-2248
2248-2249
2249-2250
2250-2251
2251-2252
2252-2253
2253-2254
2254-2255
2255-2256
2256-2257
2257-2258
2258-2259
2259-2260
2260-2261
2261-2262
2262-2263
2263-2264
2264-2265
2265-2266
2266-2267
2267-2268
2268-2269
2269-2270
2270-2271
2271-2272
2272-2273
2273-2274
2274-2275
2275-2276
2276-2277
2277-2278
2278-2279
2279-2280
2280-2281
2281-2282
2282-2283
2283-2284
2284-2285
2285-2286
2286-2287
2287-2288
2288-2289
2289-2290
2290-2291
2291-2292
2292-2293
2293-2294
2294-2295
2295-2296
2296-2297
2297-2298
2298-2299
2299-2300
2300-2301
2301-2302
2302-2303
2303-2304
2304-2305
2305-2306
2306-2307
2307-2308
2308-2309
2309-2310
2310-2311
2311-2312
2312-2313
2313-2314
2314-2315
2315-2316
2316-2317
2317-2318
2318-2319
2319-2320
2320-2321
2321-2322
2322-2323
2323-2324
2324-2325
2325-2326
2326-2327
2327-2328
2328-2329
2329-2330
2330-2331
2331-2332
2332-2333
2333-2334
2334-2335
2335-2336
2336-2337
2337-2338
2338-2339
2339-2340
2340-2341
2341-2342
2342-2343
2343-2344
2344-2345
2345-2346
2346-2347
2347-2348
2348-2349
2349-2350
2350-2351
2351-2352
2352-2353
2353-2354
2354-2355
2355-2356
2356-2357
2357-2358
2358-2359
2359-2360
2360-2361
2361-2362
2362-2363
2363-2364
2364-2365
2365-2366
2366-2367
2367-2368
2368-2369
23




FIG. 24

1. **Введение**
 2. **1.1. Актуальность темы**
 3. **1.2. Цели и задачи**
 4. **2. Теоретический анализ**
 5. **2.1. Понятие и сущность**
 6. **2.2. Классификация**
 7. **2.3. Методология**
 8. **3. Эмпирическое исследование**
 9. **3.1. Методы исследования**
 10. **3.2. Результаты**
 11. **3.3. Обсуждение**
 12. **4. Заключение**
 13. **5. Литература**
 14. **6. Приложения**
 15. **7. Заключение**




FIG. 25

FIG. 26

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Declaration and Power of Attorney For Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

DYNAMIC IMAGE COMPOSITION APPARATUS

AND METHOD

上記発明の明細書（下記の欄でx印がついていない場合は、本表に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約国際出願番号を _____ とし、
（該当する場合） _____ に訂正されました。

☒ was filed on March 10, 1999
as United States Application Number or
PCT International Application Number
PCT/JP99/01153 and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration
(日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

Prior Foreign Application(s)

外国での先行出願
10-195604(Number)
(番号)

Japan

(Country)
(国名)(Number)
(番号)(Country)
(国名)

私は、第35編米国法典119条(e)項に基づいて下記の米国外特許出願規定に記載された権利をここに主張いたします。

(Application No.)
(出願番号)(Filing Date)
(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国外特許出願に記載された権利、又は米国外を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国外特許出願に開示されていない限り、その先行米国外出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

PCT/JP99/01153

(Application No.)
(出願番号)

10th/March/1999

(Filing Date)
(出願日)(Application No.)
(出願番号)(Filing Date)
(出願日)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じているところに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の表明を行なえば、出願した、又は発明に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed

優先権主張なし

10th/July/1998

(Day/Month/Year Filed)
(出願年月日)(Day/Month/Year Filed)
(出願年月日)

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)
(出願番号)(Filing Date)
(出願日)

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

Pending

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、保属中、放棄済)(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、保属中、放棄済)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration

(日本語宣言書)

委任状: 私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。(弁理士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

James D. Halsey, Jr., 22,729; Harry John Staas, 22,010; David M. Pitcher, 25,908; John C. Garvey, 28,607; J. Randall Beckers, 30,358; William F. Herbert, 31,024; Richard A. Gollhofer, 31,106; Mark J. Henry, 36,162; Gene M. Garner II, 34,172; Michael D. Stein, 37,240; Paul I. Kravetz, 35,230; Gerald P. Joyce, III, 37,648; Todd E. Marlette, 35,269; Harlan B. Williams, Jr., 34,756; George N. Stevens, 36,938; Michael C. Soldner, P-41,455 and William M. Schertler, 35,348 (agent)

書類送付先

Send Correspondence to:

STAAS & HALSEY
700 Eleventh Street, N.W.
Suite 500
Washington, D.C. 20001

直接電話連絡先: (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

STAAS & HALSEY
(202) 434-1500

唯一または第一発明者名	Full name of sole or first inventor	
	Yasuhiro KAWAKATSU	
発明者の署名	Inventor's signature	Date
日付	<i>Yasuhiro Kawakatsu</i>	Sep. 12, 2000
住所	Residence	
	Kawasaki, Japan	
国籍	Citizenship	
	Japan	
私書箱	Post Office Address	
	c/o FUJITSU LIMITED, 1-1, Kamikodanaka	
	4-chome, Nakahara-ku, Kawasaki-shi,	
	Kanagawa 211-8588, Japan	
第二共同発明者	Full name of second joint inventor, if any	
	Yuuichirou IKEDA	
第二共同発明者	Second inventor's signature	Date
日付	<i>Yuuichirou Ikeda</i>	Sep. 12, 2000
住所	Residence	
	Kawasaki, Japan	
国籍	Citizenship	
	Japan	
私書箱	Post Office Address	
	c/o FUJITSU LIMITED, 1-1, Kamikodanaka	
	4-chome, Nakahara-ku, Kawasaki-shi,	
	Kanagawa 211-8588, Japan	

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)